




上面



側面



取付金物無



取付金物有

型 番	入力電圧	消費電力	A (mm)	B (mm)	C (mm)	D (mm)	E (mm)	F (mm)
NDP1 xxK-24V-C90	DC 24V	1W	94.7	99.8.3	12	11	10.6	10
NDP3 xxK-24V-C90	DC 24V	3W	188.2	193.3	12	11	10.6	10
NDP4 xxK-24V-C90	DC 24V	4W	279.2	284.3	12	11	10.6	10
NDP7 xxK-24V-C90	DC 24V	7W	558.7	563.8	12	11	10.6	10
NDP11 xxK-24V-C90	DC 24V	11W	837.7	842.8	12	11	10.6	10
NDP15 xxK-24V-C90	DC 24V	15W	1116.8	1121.9	12	11	10.6	10

5	最大接続数	直列接続時 最大 55W
4	入力電圧	DC 24V
3	防塵・防滴性能	IP20
2	本体	アルミニウム
1	消費電力	LED 15W / 11W / 7W / 4W / 3W / 1W

FEELUX
Feelux Lighting Co., Ltd.

株式会社FEELUX JAPAN

図 名

FLX Stix NDPro (DIVA3)

DATE

2017. 04. 04

SCALE

NONE