

TEST REPORT

1. Applicant

* Client Name :
* Address : 235-48 GWANGJEOK-RO GWANGJEOK-MYEON YANGJU-SI GYENGGI-DO 482-84
* Date of Receipt : 230512

2. Purpose of Report :

3. Number of Report : 230511

4. Test Standard / Item : / NDF3 F.F 120V 35K

5. Test Period : 230512 ~ 230512

6. Test Environment

* Ambient Temp. : 22.0 +- 3 °C
* Relative Humidity : 60.0 +- 10 % RH

7. Test Item

* Name of Product :
* Rating :
* Model :

8. Test Result : Refer to the attachment

Confirmation	Test by		Technical manager	
	PKW	Sign	PKW	Sign

- * The result shown in this test report refer only to the sample(s) tested unless otherwise stated.
- * This report cannot be reporduced, except in full.
- * This report is for reference only. It cannot replace the report by standard organization(s).

Result

Report Number	Sample Name	Sample Number	Test Standard
230511			

Test Item	Unit	Result	Notice
Beam Distribution Test		See Attachement	
ATHD	%	13.5	
CIE 1931 Cx, Cy		0.4078 , 0.3857	
Correlated Color Temperature	K	3408	
Ra		93.9	
Power Factor		0.991	
Input Voltage	V	120.33	
Input Current	A	0.021	
Input Watt	W	2.4449	
Lamp Flux	lm	185.5	
Efficient	lm/W	75.86	
luminous Intensity (Max , Center)	cd	60 , 60	
Illuminance	lx	60	1 m
		15	2 m
		7	3 m

* This test result is for the sample provided by the client.

* Sample photo

Click to load image


Luminaire KH FEELUX

Lamp

No. of lamps	1	Voltage (V)	120.33
Lamp flux (lm)	186	Current (A)	0.02051
Total flux (lm)	186	Power Factor	0.9908

Report	230511
Filename	NDF3 F.F 120V 35K.jdt
Operator	
Date	2023-05-11 오후 7:07:50

Luminous Intensity Distribution



Luminaire KH FEELUX

Lamp

No. of lamps 1

Voltage (V) 120.33

Lamp flux (lm) 186

Current (A) 0.02051

Total flux (lm) 186

Power Factor 0.9908

Report


230511

Filename NDF3 F.F 120V 35K.jdt

Operator

Date 2023-05-11 오후 7:07:50

Luminous Intensity Distribution (Lowest 10%)



Luminaire KH FEELUX

Lamp

Report

230511

No. of lamps 1

Voltage (V) 120.33

Filename NDF3 F.F 120V 35K.jdt

Lamp flux (lm) 186

Current (A) 0.02051

Operator

Total flux (lm) 186

Power Factor 0.9908

Date 2023-05-11 오후 7:07:50

Luminous Intensity Data

Maximum (cd) : 60

Minimum (cd) : 0

G/C	0	30	60	90	120	150	180	210	240	270	300	330	360
0	59.26	59.21	59.22	58.86	59.66	59.22	59.26	59.21	59.22	58.86	59.66	59.22	59.26
10	57.86	56.99	57.2	57.7	58.2	58.52	59.67	59.12	58.71	57.87	58.79	57.76	57.86
20	54.03	53.42	52.63	53.43	54.51	55.04	56.49	57.51	56.56	55.85	54.39	54.69	54.03
30	47.74	46.94	47.12	47.45	49.24	50.28	52.59	52.47	50.92	49.71	49.27	48.35	47.74
40	41.22	40.61	39.69	39.21	41.67	43.33	45.75	45.61	43.96	42.55	41.92	41.84	41.22
50	33.65	33.18	31.5	31.13	33.15	35.26	38.82	38.42	36.42	34.78	34.34	34.61	33.65
60	24.58	24.91	22.94	22.05	24.65	27.22	29.66	30.01	27.48	25.8	25.9	26.38	24.58
70	16.17	16.01	13.49	12.18	15.33	18.69	21.78	22.14	18.61	15.93	16.02	17.64	16.17
80	9.39	7.87	5.7	3.63	7.37	10.44	13.19	12.16	9.75	6.65	8.2	9.39	9.39
90	7.36	5.08	3.23	-0.16	3.24	5.15	7	5.5	3.61	0.23	3.35	5.57	7.36
100	6.89	5.54	2.8	0.16	2.34	5.62	6.99	5.07	3.12	-0.06	2.93	4.81	6.89
110	6.19	4.81	3.06	0.5	3.35	4.17	5.62	5.59	3.49	-0.3	3.33	5.65	6.19
120	2.7	4.99	0.28	0.58	0.64	5.06	2.32	5	0.01	1.09	0.63	4.76	2.7
130	0.12	0.89	1.72	0.09	0.99	0.37	0.84	1.28	1.39	0.19	1.68	1.61	0.12

Luminaire KH FEELUX

Lamp

Report

230511

No. of lamps 1

Voltage (V) 120.33

Filename NDF3 F.F 120V 35K.jdt

Lamp flux (lm) 186

Current (A) 0.02051

Operator

Total flux (lm) 186

Power Factor 0.9908

Date 2023-05-11 오후 7:07:50

Luminous Flux Table

Total Lamp Lumens: 185.47

Luminaire Efficiency (lm/W): 75.86

CIE Classification: Direct

Elevation	Lumens	Cumulative	Lamp %	Luminaire %
0	1.42	1.42	0.76	0.76
10	11.07	12.49	6.73	6.73
20	20.56	33.04	17.81	17.82
30	27.02	60.06	32.38	32.38
40	29.76	89.83	48.42	48.43
50	29.03	118.86	64.08	64.09
60	24.63	143.49	77.35	77.37
70	17.50	160.98	86.78	86.80
80	9.32	170.31	91.81	91.83
90	4.49	174.79	94.23	94.25
100	4.15	178.95	96.47	96.48
110	3.90	182.85	98.57	98.59
120	2.22	185.06	99.76	99.78
130	0.40	185.47	99.98	100.00


Luminaire KH FEELUX

Lamp

No. of lamps	1	Voltage (V)	120.33
Lamp flux (lm)	186	Current (A)	0.02051
Total flux (lm)	186	Power Factor	0.9908

Report	230511
Filename	NDF3 F.F 120V 35K.jdt
Operator	
Date	2023-05-11 오후 7:07:50

IsoCandela (Type C)




Luminaire KH FEELUX

Lamp

No. of lamps	1	Voltage (V)	120.33
Lamp flux (lm)	186	Current (A)	0.02051
Total flux (lm)	186	Power Factor	0.9908

Report	230511
Filename	NDF3 F.F 120V 35K.jdt
Operator	
Date	2023-05-11 오후 7:07:50

IsoLux Diagram (Ground)



Pole Height (m): 2.7

Area Width (m): 12

Total Optical Solution Provider

Luminaire KH FEELUX

Lamp

No. of lamps 1

Voltage (V) 120.33

Lamp flux (lm) 186

Current (A) 0.02051

Total flux (lm) 186

Power Factor 0.9908

Report


230511

Filename NDF3 F.F 120V 35K.jdt

Operator

Date 2023-05-11 오후 7:07:50

IsoLux Diagram (Wall)



Pole Height (m): 2.7

Wall Distance (m): 2.7

Aiming Plane: 0

Wall Height (m): 12

Total Optical Solution Provider

Luminaire KH FEELUX

Lamp

No. of lamps	1	Voltage (V)	120.33
Lamp flux (lm)	186	Current (A)	0.02051
Total flux (lm)	186	Power Factor	0.9908

Report 230511

Filename NDF3 F.F 120V 35K.jdt

Operator

Date 2023-05-11 오후 7:07:50

Illuminance Levels (Ground)

6.00	0.08	0.11	0.08	0.12	0.14	0.15	0.16	0.15	0.15	0.12	0.08	0.11	0.09
5.00	0.12	0.09	0.13	0.17	0.37	0.42	0.44	0.41	0.37	0.18	0.14	0.11	0.11
4.00	0.11	0.16	0.31	0.44	0.48	0.57	0.62	0.57	0.49	0.45	0.32	0.15	0.10
3.00	0.12	0.23	0.49	0.54	1.09	1.23	1.34	1.24	1.10	0.57	0.47	0.21	0.13
2.00	0.16	0.38	0.49	1.20	1.59	2.61	2.99	2.55	1.63	1.14	0.49	0.38	0.16
1.00	0.22	0.50	0.71	1.29	2.64	4.74	6.51	4.66	2.56	1.27	0.64	0.46	0.19
0.00	0.24	0.55	0.80	1.65	3.43	6.74	8.13	6.53	3.09	1.44	0.68	0.47	0.19
-1.00	0.21	0.49	0.70	1.46	2.88	5.11	6.54	4.85	2.64	1.31	0.64	0.45	0.18
-2.00	0.20	0.44	0.59	1.29	1.86	2.86	3.21	2.65	1.69	1.17	0.51	0.39	0.16
-3.00	0.17	0.26	0.55	0.68	1.23	1.43	1.49	1.31	1.18	0.59	0.49	0.22	0.13
-4.00	0.13	0.19	0.38	0.52	0.58	0.66	0.71	0.67	0.51	0.49	0.34	0.16	0.11
-5.00	0.14	0.14	0.18	0.23	0.43	0.47	0.49	0.48	0.39	0.21	0.15	0.10	0.12
-6.00	0.11	0.13	0.12	0.17	0.19	0.19	0.19	0.20	0.16	0.13	0.10	0.12	0.09
-6.00	-5.00	-4.00	-3.00	-2.00	-1.00	0.00	1.00	2.00	3.00	4.00	5.00	6.00	

Illum. (Max.) : 8.1288

Illum. (Min.) : 0.0774

Illum. (Avg.) : 0.9426

All illuminance level values are in lux.



Luminaire KH FEELUX

Lamp

No. of lamps 1

Voltage (V) 120.33

Lamp flux (lm) 186

Current (A) 0.02051

Total flux (lm) 186

Power Factor 0.9908

Report


230511

Filename NDF3 F.F 120V 35K.jdt

Operator

Date 2023-05-11 오후 7:07:50

Illuminance Cone Diagram



Luminaire KH FEELUX

Lamp

Report 230511

No. of lamps 1 Voltage (V) 120.33

Filename NDF3 F.F 120V 35K.jdt

Lamp flux (lm) 186 Current (A) 0.02051

Operator

Total flux (lm) 186 Power Factor 0.9908

Date 2023-05-11 오후 7:07:50

Coefficient of Utilization

	Refl. Ceiling (%)	80%	80%	80%	70%	70%	70%	50%	50%	50%	30%	30%	30%	10%	10%	10%	0%
	Refl. Wall (%)	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0%
Eff. Floor Cavity	Refl.	20%	20%	20%	20%	20%	20%	20%	20%	20%	20%	20%	20%	20%	20%	20%	20%
Room CR	0	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Room CR	1	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Room CR	2	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Room CR	3	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Room CR	4	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Room CR	5	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Room CR	6	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Room CR	7	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Room CR	8	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Room CR	9	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Room CR	10	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00