



- 位相調光対応 (マッチングテスト要)
- 最大直列W数 400W

番号	部品名	材質	備考
①	本体	アルミ押し出し材	
②	カバー	樹脂 (乳白)	
③	エンドキャップA	樹脂 (グレー)	
④	エンドキャップB	樹脂 (グレー)	
⑤	取付金具	ステンレス	
⑥	マグネット		

型番	NDF3-***K-110V-C90				NDF5-***K-110V-C90				NDF10-***K-110V-C90				NDF15-***K-110V-C90				NDF20-***K-110V-C90			
消費電力	2.5W				5W				10W				15W				20W			
入力電圧	AC100V				AC100V				AC100V				AC100V				AC100V			
各寸法 (mm)	A147, B156, C19, D18, E18, F+16.8				A282.5, B291.5, C19, D18, E18, F+16.8				A560.5, B569.5, C19, D18, E18, F+16.8				A839, B848, C19, D18, E18, F+16.8				A1117, B1126, C19, D18, E18, F+16.8			
色温度	2700K	3000K	3500K	4000K	2700K	3000K	3500K	4000K	2700K	3000K	3500K	4000K	2700K	3000K	3500K	4000K	2700K	3000K	3500K	4000K
全光束	168.2lm/m	113.1lm/m	185.5lm/m	113.1lm/m	372.1lm/m	391lm/m	402.7lm/m	377.7lm/m	754.9lm/m	716.9lm/m	829.7lm/m	759.6lm/m	1114.4lm/m	1100.9lm/m	1089.8lm/m	1143.3lm/m	1478.2lm/m	1466.1lm/m	1648.5lm/m	1521.3lm/m
使用温度	0 ~ 40℃																			
使用環境	屋内専用 (IP20)																			
	*1 型番内の***には色温度の上2桁があてはまります。																			