

TEST REPORT

1. Applicant

* Client Name :
* Address : 235-48 GWANGJEOK-RO GWANGJEOK-MYEON YANGJU-SI GYENGGI-DO 482-84
* Date of Receipt : 230804

2. Purpose of Report :

3. Number of Report : 230804

4. Test Standard / Item : / 230804 FNL 3D 30K-24V-C90-1M-45D

5. Test Period : 230804 ~ 230804

6. Test Environment

* Ambient Temp. : 22.0 +- 3 °C
* Relative Humidity : 60.0 +- 10 % RH

7. Test Item

* Name of Product :
* Rating :
* Model :

8. Test Result : Refer to the attachment

Confirmation	Test by		Technical manager	
	JSY	Sign	JSY	Sign

- * The result shown in this test report refer only to the sample(s) tested unless otherwise stated.
- * This report cannot be reporduced, except in full.
- * This report is for reference only. It cannot replace the report by standard organization(s).

Result

Report Number	Sample Name	Sample Number	Test Standard
230804			

Test Item	Unit	Result	Notice
Beam Distribution Test		See Attachement	
ATHD	%	0.0	
CIE 1931 Cx, Cy		0.4435 , 0.4073	
Correlated Color Temperature	K	2919	
Ra		91.27	
Power Factor		1.000	
Input Voltage	V	23.901	
Input Current	A	0.800	
Input Watt	W	19.116	
Lamp Flux	lm	1522.3	
Efficient	lm/W	79.63	
luminous Intensity (Max , Center)	cd	1756 , 1756	
Illuminance	lx	1756	1 m
		439	2 m
		195	3 m

* This test result is for the sample provided by the client.

* Sample photo

Click to load image

Luminaire KH FEELUX

Lamp

Report

230804

No. of lamps 1

Voltage (V)

23.90Filename 230804 FNL 3D 30K-24V-C90-1M-45D.jdt

Lamp flux (lm) 1522

Current (A)

0.795Operator


Total flux (lm) 1522

Power Factor

Date

2023-08-04 오후 12:12:26

Luminous Intensity Distribution



Luminaire KH FEELUX

Lamp

Report

230804

No. of lamps 1

Voltage (V)

23.90Filename 230804 FNL 3D 30K-24V-C90-1M-45D.jdt

Lamp flux (lm) 1522

Current (A)

0.795Operator


Total flux (lm) 1522

Power Factor

Date

2023-08-04 오후 12:12:26

Luminous Intensity Distribution (Lowest 10%)



Luminaire KH FEELUX

Lamp

Report

230804

No. of lamps 1

Voltage (V)

23.90Filename 230804 FNL 3D 30K-24V-C90-1M-45D.jdt

Lamp flux (lm) 1522

Current (A)

0.795Operator

Total flux (lm) 1522

Power Factor

Date

2023-08-04 오후 12:12:26

Luminous Intensity Data

Maximum (cd) : 1756

Minimum (cd) : 1

G/C	0	30	60	90	120	150	180	210	240	270
0	1756.26	1706.16	1705.35	1691.37	1711.3	1627.82	1756.26	1706.16	1705.35	1691.37
10	1195.7	1217.84	1371.67	1261.52	1211.92	1065.74	1680.3	1730.77	1665.5	1721.47
20	664.4	647.17	749.38	713.79	711.33	632.74	1166.2	1172.49	1178.25	1191.52
30	356.84	372.43	413.6	418.96	398.62	353.35	614.66	661.33	631.91	682.56
40	215.93	224.55	245.92	251.98	241.57	217.22	357.27	363.06	367.98	372.22
50	120.49	142.96	159.98	166.99	160.81	142.09	216.89	219.89	223.02	223.18
60	54.88	64.62	98.58	106.58	100.86	66.9	130.43	143.25	149.58	150.45
70	25.18	28.27	44.25	53.42	44.06	30.13	59.46	70.7	92.96	96.84
80	5.45	7.29	10.56	15.2	12.23	8.17	28.58	30.8	40.56	46.78
90	1	1.67	2.24	3.16	2.05	1.35	7.63	8.85	10.52	11.09
100	1.48	1.88	1.96	1.52	0.7	1.32	0.53	0.81	2.31	1.77
110	2.4	2.13	2.88	2.35	2.63	2.22	0.88	1.14	1.89	1.44
120	3.32	3.79	3.45	3.38	3.24	2.72	2.37	2.54	2.18	2.88
130	4.32	5.01	4.44	4.84	4.55	5.78	3.17	3.04	2.8	2.99

Luminaire KH FEELUX

Lamp

Report

230804

No. of lamps 1

Voltage (V)

23.90Filename 230804 FNL 3D 30K-24V-C90-1M-45D.jdt

Lamp flux (lm) 1522

Current (A)

0.795Operator

Total flux (lm) 1522

Power Factor

Date

2023-08-04 오후 12:12:26

Luminous Intensity Data (Continued)

Maximum (cd) : 1756

Minimum (cd) : 1

G/C	300	330	360
0	1711.3	1627.82	1756.26
10	1662.96	1713.47	1195.7
20	1183.61	1204.4	664.4
30	632.9	676.62	356.84
40	364.59	365.86	215.93
50	218.75	218.79	120.49
60	144.95	142.41	54.88
70	89.78	66	25.18
80	38.72	27.84	5.45
90	8.55	7.65	1
100	1.05	1.14	1.48
110	1.61	1.1	2.4
120	1.91	2.01	3.32
130	3.17	2.44	4.32

Luminaire KH FEELUX

Lamp

Report

230804

No. of lamps 1

Voltage (V)

23.90Filename 230804 FNL 3D 30K-24V-C90-1M-45D.jdt

Lamp flux (lm) 1522

Current (A)

0.795Operator

Total flux (lm) 1522

Power Factor

Date

2023-08-04 오후 12:12:26

Luminous Flux Table

Total Lamp Lumens: 1522.3

Luminaire Efficiency (lm/W): 79.63

CIE Classification: Direct

Elevation	Lumens	Cumulative	Lamp %	Luminaire %
0	40.64	40.64	2.67	2.67
10	277.34	317.97	20.89	20.89
20	350.09	668.07	43.89	43.89
30	283.56	951.63	62.51	62.51
40	210.51	1162.14	76.34	76.34
50	154.78	1316.92	86.51	86.51
60	106.98	1423.90	93.54	93.54
70	60.12	1484.03	97.49	97.49
80	24.46	1508.49	99.09	99.09
90	6.00	1514.49	99.49	99.49
100	1.48	1515.97	99.58	99.59
110	1.95	1517.92	99.71	99.71
120	2.67	1520.59	99.89	99.89
130	1.69	1522.28	100.00	100.00

Luminaire KH FEELUX

Lamp

Report

230804

No. of lamps 1

Voltage (V)

23.90Filename 230804 FNL 3D 30K-24V-C90-1M-45D.jdt

Lamp flux (lm) 1522

Current (A)

0.795Operator


Total flux (lm) 1522

Power Factor

Date

2023-08-04 오후 12:12:26

IsoCandela (Type C)



Luminaire KH FEELUX

Lamp

Report

230804

No. of lamps 1

Voltage (V)

23.90Filename 230804 FNL 3D 30K-24V-C90-1M-45D.jdt

Lamp flux (lm) 1522

Current (A)

0.795Operator


Total flux (lm) 1522

Power Factor

Date

2023-08-04 오후 12:12:26

IsoLux Diagram (Ground)



Pole Height (m): 2.7

Area Width (m): 12

Total Optical Solution Provider

Luminaire KH FEELUX

Lamp

Report

230804

No. of lamps 1

Voltage (V)

23.90Filename 230804 FNL 3D 30K-24V-C90-1M-45D.jdt

Lamp flux (lm) 1522

Current (A)

0.795Operator


Total flux (lm) 1522

Power Factor

Date

2023-08-04 오후 12:12:26

IsoLux Diagram (Wall)



Pole Height (m): 2.7

Wall Distance (m): 2.7

Aiming Plane: 0

Wall Height (m): 12

Total Optical Solution Provider

Luminaire KH FEELUX

Lamp

No. of lamps	1	Voltage (V)	23.901
Lamp flux (lm)	1522	Current (A)	0.7998
Total flux (lm)	1522	Power Factor	1

Report

230804

Filename 230804 FNL 3D 30K-24V-C90-1M-45D.jdt

Operator

Date

2023-08-04 오후 12:12:26

Illuminance Levels (Ground)



6.00	0.35	0.48	0.33	0.40	0.54	0.63	0.72	0.66	0.40	0.27	0.27	0.40	0.20
5.00	0.35	0.33	0.53	0.80	1.76	2.11	2.31	2.13	1.52	0.71	0.43	0.18	0.26
4.00	0.20	0.37	1.50	2.29	2.05	2.75	3.14	2.76	1.46	2.14	1.09	0.28	0.16
3.00	0.38	0.50	1.98	2.52	6.61	6.28	7.55	5.77	6.39	1.65	1.68	0.40	0.25
2.00	0.45	1.66	1.97	5.79	8.78	15.58	22.06	14.57	7.42	5.53	1.37	1.38	0.31
1.00	0.68	2.41	2.86	5.91	15.32	45.80	140.70	41.31	14.35	5.20	2.81	2.34	0.71
0.00	0.85	2.98	3.97	10.05	31.79	188.19	240.91	133.31	18.85	5.73	1.95	1.62	0.36
-1.00	0.53	2.16	2.76	8.48	23.39	72.77	192.79	74.62	23.49	8.49	2.67	2.01	0.51
-2.00	0.74	2.38	2.85	9.26	12.21	23.47	34.16	23.53	12.42	9.43	2.90	2.39	0.83
-3.00	0.60	0.96	3.00	3.33	9.50	8.57	10.38	8.55	9.58	3.52	3.04	1.05	0.70
-4.00	0.38	0.67	1.99	3.09	2.89	3.91	4.32	3.91	2.91	3.09	2.06	0.75	0.43
-5.00	0.61	0.45	0.84	1.22	2.41	2.92	3.11	2.92	2.41	1.25	0.89	0.61	0.65
-6.00	0.46	0.68	0.55	0.62	0.83	1.07	1.13	1.06	0.91	0.72	0.58	0.69	0.52
-6.00	-5.00	-4.00	-3.00	-2.00	-1.00	0.00	1.00	2.00	3.00	4.00	5.00	6.00	

Illum. (Max.) : 240.91

Illum. (Min.) : 0.1607

Illum. (Avg.) : 10.435

All illuminance level values are in lux.



Luminaire KH FEELUX

Lamp

Report

230804

No. of lamps 1

Voltage (V)

23.90Filename 230804 FNL 3D 30K-24V-C90-1M-45D.jdt

Lamp flux (lm) 1522

Current (A)

0.795Operator


Total flux (lm) 1522

Power Factor

Date

2023-08-04 오후 12:12:26

Illuminance Cone Diagram



Luminaire KH FEELUX

Lamp

Report

230804

No. of lamps 1 Voltage (V) 23.901

Filename 230804 FNL 3D 30K-24V-C90-1M-45D.jdt

Lamp flux (lm) 1522 Current (A) 0.7998

Operator

Total flux (lm) 1522 Power Factor 1

Date 2023-08-04 오후 12:12:26

Coefficient of Utilization

	Refl. Ceiling (%)	80%	80%	80%	70%	70%	70%	50%	50%	50%	30%	30%	30%	10%	10%	10%	0%
	Refl. Wall (%)	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0%
Eff. Floor Cavity Refl.		20%	20%	20%	20%	20%	20%	20%	20%	20%	20%	20%	20%	20%	20%	20%	20%
Room CR 0		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Room CR 1		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Room CR 2		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Room CR 3		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Room CR 4		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Room CR 5		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Room CR 6		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Room CR 7		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Room CR 8		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Room CR 9		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Room CR 10		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00