

# TEST REPORT

**1. Applicant**

\* Client Name :  
\* Address : 235-48 GWANGJEOK-RO GWANGJEOK-MYEON YANGJU-SI GYENGGI-DO 482-84  
\* Date of Receipt : 230508

**2. Purpose of Report :**

**3. Number of Report :** 230508

**4. Test Standard / Item :** / FNL3D-27K-C90-35도-1m

**5. Test Period :** 230508 ~ 230508

**6. Test Environment**

\* Ambient Temp. : 22.0 +- 3 °C  
\* Relative Humidity : 60.0 +- 10 % RH

**7. Test Item**

\* Name of Product :  
\* Rating :  
\* Model :

**8. Test Result :** Refer to the attachment

Confirmation	Test by		Technical manager	
	PKW	Sign	PKW	Sign

\*\*\*\*\*

- \* The result shown in this test report refer only to the sample(s) tested unless otherwise stated.
- \* This report cannot be reporduced, except in full.
- \* This report is for reference only. It cannot replace the report by standard organization(s).

## Result

Report Number	Sample Name	Sample Number	Test Standard
230508			

Test Item	Unit	Result	Notice
Beam Distribution Test		See Attachement	
ATHD	%	0.0	
CIE 1931 Cx, Cy		0.4682 , 0.4187	
Correlated Color Temperature	K	2647	
Ra		91.47	
Power Factor		1.000	
Input Voltage	V	23.910	
Input Current	A	0.762	
Input Watt	W	18.222	
Lamp Flux	lm	1453.5	
Efficient	lm/W	79.77	
luminous Intensity (Max , Center)	cd	2169 , 2169	
Illuminance	lx	2169	1 m
		542	2 m
		241	3 m

\* This test result is for the sample provided by the client.

\* Sample photo

Click to load image

Luminaire KH FEELUX

Lamp

Report

230508

No. of lamps 1

Voltage (V) 23.91

Filename FNL3D-27K-C90-35도-1m.jdt

Lamp flux (lm) 1454

Current (A) 0.7621


Operator

Total flux (lm) 1454

Power Factor 1

Date 2023-05-08 오후 5:20:18

## Luminous Intensity Distribution



Luminaire KH FEELUX

Lamp

Report

230508

No. of lamps 1

Voltage (V) 23.91

Filename FNL3D-27K-C90-35도-1m.jdt

Lamp flux (lm) 1454

Current (A) 0.7621


Operator

Total flux (lm) 1454

Power Factor 1

Date 2023-05-08 오후 5:20:18

## Luminous Intensity Distribution (Lowest 10%)



Luminaire KH FEELUX

Lamp

Report

230508

No. of lamps 1

Voltage (V) 23.91

Filename FNL3D-27K-C90-35도-1m.jdt

Lamp flux (lm) 1454

Current (A) 0.7621

Operator

Total flux (lm) 1454

Power Factor 1

Date 2023-05-08 오후 5:20:18

## Luminous Intensity Data

Maximum (cd) : 2169

Minimum (cd) : 0

G/C	0	30	60	90	120	150	180	210	240	270
0	2168.57	2161.91	2161.04	2154.22	2145.84	2136.93	2168.57	2161.91	2161.04	2154.22
10	1786.98	1641.74	1858.77	1760.18	1916.58	1724.08	1783.63	1921.14	1745.65	1869.54
20	788.84	752.3	918.88	934.08	1006.13	827.32	843.92	930.88	861.23	923.24
30	379.16	392.99	451.1	501.9	496.45	424.08	424.57	434.38	442.65	440.23
40	221.59	230.16	258.04	275.13	273.92	237.38	233.44	239.41	250.57	251.79
50	148.29	153.9	173.45	183.56	180.88	156.97	154.01	157.66	169.19	172.32
60	93.07	103.15	116.23	130.65	118.26	100.03	86.05	102.19	111.01	122.22
70	38.06	46.42	66.38	77.22	67.9	40.94	36.61	41.39	61.16	72.9
80	12.62	14.42	22.82	28.86	22.58	13.31	11.31	12.57	18	23.57
90	1.94	3.25	3.34	5.28	4.17	2.23	1.57	1.8	1.54	2.95
100	1.41	1.39	0.85	0.36	0.63	0.58	1.08	1.57	1.22	1.16
110	1.24	1.21	1.71	0.51	1.14	1.62	0.84	0.82	2.26	1.75
120	1.72	2.43	1.93	2.17	2.11	1.68	1	2.06	2.44	2.8
130	3.52	4.12	2.95	3.9	2.48	3.94	3.41	3.74	4.02	3.58

Luminaire KH FEELUX

Lamp

Report

230508

No. of lamps 1

Voltage (V) 23.91

Filename FNL3D-27K-C90-35도-1m.jdt

Lamp flux (lm) 1454

Current (A) 0.7621

Operator

Total flux (lm) 1454

Power Factor 1

Date 2023-05-08 오후 5:20:18

## Luminous Intensity Data (Continued)

Maximum (cd) : 2169

Minimum (cd) : 0

G/C	300	330	360
0	2145.84	2136.93	2168.57
10	1679.67	1818.12	1786.98
20	806.56	843.88	788.84
30	415.63	401.96	379.16
40	241.81	231.37	221.59
50	165.95	153.38	148.29
60	111.14	102.84	93.07
70	60.91	47.35	38.06
80	18.96	14.55	12.62
90	2.81	2.54	1.94
100	1.45	1.13	1.41
110	2.38	1.73	1.24
120	3.03	2.49	1.72
130	4.07	3.03	3.52

Luminaire KH FEELUX

Lamp

Report

230508

No. of lamps 1

Voltage (V) 23.91

Filename FNL3D-27K-C90-35도-1m.jdt

Lamp flux (lm) 1454

Current (A) 0.7621

Operator

Total flux (lm) 1454

Power Factor 1

Date 2023-05-08 오후 5:20:18

## Luminous Flux Table

Total Lamp Lumens: 1453.5

Luminaire Efficiency (lm/W): 79.77

CIE Classification: Direct

Elevation	Lumens	Cumulative	Lamp %	Luminaire %
0	51.52	51.52	3.54	3.54
10	340.84	392.36	26.99	26.99
20	325.81	718.17	49.41	49.41
30	237.53	955.70	65.75	65.75
40	172.75	1128.45	77.64	77.64
50	137.70	1266.16	87.11	87.11
60	102.51	1368.66	94.16	94.16
70	56.37	1425.03	98.04	98.04
80	19.20	1444.23	99.36	99.36
90	3.05	1447.28	99.57	99.57
100	1.15	1448.43	99.65	99.65
110	1.48	1449.91	99.75	99.75
120	2.04	1451.95	99.89	99.89
130	1.55	1453.50	100.00	100.00

Luminaire KH FEELUX

Lamp

Report

230508

No. of lamps 1

Voltage (V) 23.91

Filename FNL3D-27K-C90-35도-1m.jdt

Lamp flux (lm) 1454

Current (A) 0.7621


Operator

Total flux (lm) 1454

Power Factor 1

Date 2023-05-08 오후 5:20:18

## IsoCandela (Type C)





Luminaire KH FEELUX

Lamp

Report

230508

No. of lamps 1

Voltage (V) 23.91

Filename FNL3D-27K-C90-35도-1m.jdt

Lamp flux (lm) 1454

Current (A) 0.7621


Operator

Total flux (lm) 1454

Power Factor 1

Date 2023-05-08 오후 5:20:18

## IsoLux Diagram (Ground)



Pole Height (m): 2.7

Area Width (m): 12

Total Optical Solution Provider

Luminaire KH FEELUX

Lamp

Report

230508

No. of lamps 1

Voltage (V) 23.91

Filename FNL3D-27K-C90-35도-1m.jdt

Lamp flux (lm) 1454

Current (A) 0.7621


Operator

Total flux (lm) 1454

Power Factor 1

Date 2023-05-08 오후 5:20:18

## IsoLux Diagram (Wall)



Pole Height (m): 2.7

Wall Distance (m): 2.7

Aiming Plane: 0

Wall Height (m): 12

Total Optical Solution Provider

Luminaire KH FEELUX

Lamp

No. of lamps	1	Voltage (V)	23.91
Lamp flux (lm)	1454	Current (A)	0.7621
Total flux (lm)	1454	Power Factor	1

Report 230508

Filename FNL3D-27K-C90-35도-1m.jdt

Operator

Date 2023-05-08 오후 5:20:18

## Illuminance Levels (Ground)



6.00	0.43	0.58	0.47	0.56	0.73	0.82	0.95	0.86	0.59	0.42	0.39	0.51	0.33
5.00	0.48	0.48	0.72	1.05	1.99	2.33	2.57	2.37	1.75	0.92	0.61	0.29	0.44
4.00	0.28	0.52	1.71	2.56	2.40	3.17	3.65	3.19	2.09	2.35	1.40	0.45	0.25
3.00	0.53	0.72	2.25	2.95	7.26	7.00	8.29	6.21	6.74	2.36	2.07	0.66	0.40
2.00	0.62	1.90	2.33	6.38	9.76	17.69	25.18	15.01	8.06	5.89	2.04	1.67	0.50
1.00	0.54	1.99	2.54	6.61	17.41	58.17	196.09	45.45	14.74	5.84	2.60	1.97	0.61
0.00	0.55	2.10	2.72	6.97	21.34	198.33	297.47	198.49	19.66	6.69	2.77	2.05	0.58
-1.00	0.56	2.01	2.56	6.02	15.41	51.24	208.02	50.62	15.48	6.19	2.59	1.95	0.57
-2.00	0.47	1.69	2.02	6.17	8.37	15.53	22.58	15.63	8.92	6.14	2.20	1.78	0.60
-3.00	0.37	0.62	2.12	2.32	6.60	6.24	7.73	6.47	6.66	2.75	2.18	0.76	0.49
-4.00	0.24	0.43	1.41	2.31	2.07	3.03	3.42	3.02	2.24	2.39	1.60	0.54	0.31
-5.00	0.41	0.27	0.57	0.86	1.75	2.25	2.42	2.23	1.85	0.98	0.67	0.44	0.48
-6.00	0.31	0.49	0.36	0.39	0.55	0.81	0.89	0.77	0.67	0.51	0.44	0.55	0.40
-6.00	-5.00	-4.00	-3.00	-2.00	-1.00	0.00	1.00	2.00	3.00	4.00	5.00	6.00	

Illum. (Max.) : 297.47

Illum. (Min.) : 0.2358

Illum. (Avg.) : 10.961

All illuminance level values are in lux.





Luminaire KH FEELUX

Lamp

No. of lamps 1

Voltage (V) 23.91

Lamp flux (lm) 1454

Current (A) 0.7621

Total flux (lm) 1454

Power Factor 1

Report


230508

Filename FNL3D-27K-C90-35도-1m.jdt

Operator

Date 2023-05-08 오후 5:20:18

## Illuminance Cone Diagram



Luminaire KH FEELUX

Lamp

Report 230508

No. of lamps 1 Voltage (V) 23.91

Filename FNL3D-27K-C90-35도-1m.jdt

Lamp flux (lm) 1454 Current (A) 0.7621

Operator

Total flux (lm) 1454 Power Factor 1

Date 2023-05-08 오후 5:20:18

## Coefficient of Utilization

	Refl. Ceiling (%)	80%	80%	80%	70%	70%	70%	50%	50%	50%	30%	30%	30%	10%	10%	10%	0%
	Refl. Wall (%)	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0%
Eff. Floor Cavity	Refl.	20%	20%	20%	20%	20%	20%	20%	20%	20%	20%	20%	20%	20%	20%	20%	20%
Room CR	0	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Room CR	1	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Room CR	2	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Room CR	3	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Room CR	4	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Room CR	5	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Room CR	6	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Room CR	7	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Room CR	8	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Room CR	9	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Room CR	10	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00